



# TAILIN®

## Type 1 Cutting Wheels Reinforced



TAILIN Type 1 Cutting Wheels manufactures wide range of type 1 reinforced cutting wheel for all applications, with high performance, cutting speed and blade life .

TAILIN Type 1 Cutting Wheels are used on pneumatic mini cutter, angle grinder, circular saws, portable chop saws, stationary saws, high speed saws and street saws.

TAILIN Type 1 Cutting Wheels type 1 cutting wheels are constructed of quality abrasive grains; unique weave of extra high tensile fiberglass reinforcing and specially formulated resin bonds, offering a reliable performance and safety strength.

SIZE		MAX. R.P.M.			STANDARD PACKING			N.W.	G.W	MESMT
mm	inches	Low Speed 80 m/s (1g)	80 m/s (2g)	100 m/s	PCS/SINGLE	PCS/INNER BOX	PCS/CARTON	KGS/CARTON	KGS/CARTON	CFT
75x0.8x9.53	3x1/32x3/8			25,000	25	100	500	5.7	6.8	03.1
75x1.6x9.53	3x1/16x3/8			25,000	25	100	500	9.5	10.6	0.45
100x0.5x9.53	4x1/32x3/8			18,000	25	100	500	10.3	11.4	0.58
100x1.6x9.53	4x1/16x3/8			18,000	25	100	500	16.8	17.9	0.78
100.3x16	4x1/8x5/8	13,700	15,300		50	300	600	34.2	36.2	1.28
115x3x22	4-1/2x1/8x7/8	11,900	13,300		50	300	600	44.4	46.8	1.83
125x3x22	5x1/8x7/8	11,000	12,200		50	300	600	52.8	55.5	1.84
150x3x22	6x1/8x7/8	9,100	10,200		25	100	200	25.6	27.8	1.16
180x3x22	7x1/8x7/8	7,600	8,500		25	50	200	37.2	39.7	1.39
205x3x22	8x1/8x7/8	6,700	7,500		25	50	100	24.2	25.8	0.96
230x3x22	9x1/8x7/8	6,000	6,600		25	50	100	30.2	32.3	1.08
255x3x25.4	10x1/8x1	5,400	6,000	7,500	25		100	37.0	40.3	1.32
305x3x25.4	12x1/8x1	4,500	5,000	6,300	25		50	26.8	28.2	0.92
355x3x25.4	14x1/8x1	3,900	4,300	5,400	25		50	38.5	40.3	1.22
405x3x25.4	16x1/8x1	3,000	3,800	4,800	25		25	25.8	26.9	0.67
455x4x25.4	18x5/32x1		3,400		10		10	15.2	16.6	0.72
510x4x25.4	20x5/32x1		3,000		10		10	19.1	20.6	0.84